

Dual-Port USB Car Charger, Quick Charge - Dual USB-A 3.0, UL 2089 Certified

MODEL NUMBER: U280-C02-S-QC3U



Quick-charge USB car charger safely charges two mobile devices, including tablets and smartphones, in your vehicle at the same time.

Features

Quick-Charge USB Car Charger Charges 2 Mobile Devices in Your Vehicle Simultaneously This dual USB car charger with Qualcomm Quick Charge 3.0 technology lets you quickly and safely charge two USB-powered mobile devices at the same time. You and a passenger can connect your smartphones, tablets or MP3 players, to name just a few compatible devices, to ensure satisfactory battery charge when you reach your destination. The dual-port USB car charger is certified to UL 2089 standards for vehicle battery adapters rated 24V DC or less.

USB-C PD Charging Port Charges up to 4 Times Faster Than Conventional 5W Chargers One of the two charging ports is powered by advanced Quick Charge 3.0 technology. Instead of charging at a preset power level, this charger adjusts to one of three possible power levels to provide as much power as your QC-compliant device's battery can handle. Available outputs include 3.6–6.5V 3A, 6.5–9V 2A and 9–12V 1.5A.

Built-In Auto-Sensing Adjusts to Proper Power Level The second USB port features auto-sensing technology that detects the connected device and automatically adjusts to the appropriate power level up to 5V 2.4A, perfect for fast-charging tablets and e-readers. It's compatible with Apple, Android, Windows and Amazon devices with USB-C, Thunderbolt 3 or USB-A charging ports.

Works with the 12V DC Power Outlet in Your Vehicle The compact dual USB car charger adapter connects to any standard 12V DC vehicle power outlet, such as the one on your dashboard. Just plug it in, and connect your devices' USB cables for fast, convenient mobile charging. An easy-to-see LED indicates the charger is receiving power.

Highlights

- Dual USB car charger connects to the 12V DC power outlet in your car, truck or SUV
- Ideal for charging Apple, Android, Windows and Amazon devices while traveling
- Auto-sensing USB port adjusts charging power level to your device up to 5V 2.4A
- Achieves UL 2089 certification for vehicle battery adapters rated up to 24V DC

Applications

- Charge a smartphone and a tablet or an Amazon Kindle Fire and a digital camera while driving to your destination
- Keep your Chromebook or MacBook constantly charged while on the road

System Requirements

- Vehicle with standard 12V DC power outlet

Package Includes

- U280-C02-S-QC3U USB Car Charger, Quick Charge

Specifications

| OVERVIEW | |
|--------------|--------------|
| UPC Code | 037332218230 |
| Product Type | Car Charger |



Powering Business Worldwide

TRIPP-LITE
by **EAT•N**

| | |
|--|--|
| Charging Form Factor | Direct Plug-In |
| Device Compatibility | Phone; Tablet; Amazon Kindle |
| INPUT | |
| Nominal Input Voltage(s) Supported | 12V DC |
| Input Plug Type | Car Auxiliary Power Outlet |
| OUTPUT | |
| Overload Protection | Yes |
| POWER | |
| Power Consumption (Watts) | 30 |
| CONNECTIONS | |
| Number of Ports | 2 |
| Side A - Connector 1 | Car Cigarette Lighter |
| Side B - Connector 1 | (2) USB A (FEMALE) |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Blue (Power) |
| CHARGING | |
| Number of Charging Ports | 2 |
| Total Charging Amps | 3.5A |
| Total Charging Watts | 30 |
| Charging Method | USB |
| Charging Method Detail | Quick Charge 3.0 |
| Charging Port Type | (2) USB A (FEMALE) |
| Charging Ports Details | USB-A: 3.6V~6.5V/3A, 6.5V~9V/2A, 9V~12V/1.5A |
| Charging Ports / Amps | (1) 2.4A; (1) 3A / 2A / 1.5A |
| PHYSICAL | |
| Color | White |
| Material of Construction | Polycarbonate, ABS UL94V-0 |
| Shipping Dimensions (hwd / in.) | 1.00 x 4.00 x 6.00 |
| Shipping Dimensions (hwd / cm) | 2.54 x 10.16 x 15.24 |
| Shipping Weight (lbs.) | 0.07 |
| Shipping Weight (kg) | 0.03 |
| Unit Dimensions (hwd / in.) | 1.480 x 2.780 x 1.000 |



Powering Business Worldwide



| | |
|--------------------------------------|-------------------------------------|
| Unit Dimensions (hwd / cm) | 3.75 x 7.05 x 2.55 |
| Unit Packaging Type | Polybag |
| Unit Weight (lbs.) | 0.06 |
| Unit Weight (kg) | 0.03 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range | 30 TO 90% RH, Non-Condensing |
| Storage Humidity Range | 10 TO 90% RH, Non-Condensing |
| FEATURES & SPECIFICATIONS | |
| GaN Technology | No |
| Overcurrent Protection | Yes |
| Overvoltage Protection | Yes |
| Quick Charge Compliant | 3.0 |
| Driver Required | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | UL 2089 |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.